



(12) **United States Patent**
Yamamoto

(10) **Patent No.:** **US 9,636,909 B2**
(45) **Date of Patent:** ***May 2, 2017**

(54) **DRIVING DEVICE FOR DRIVING
PIEZOELECTRIC ELEMENT**

(71) Applicant: **SEIKO EPSON CORPORATION,**
Tokyo (JP)

(72) Inventor: **Toshiyuki Yamamoto,** Nagano (JP)

(73) Assignee: **Seiko Epson Corporation,** Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/953,880**

(22) Filed: **Nov. 30, 2015**

(65) **Prior Publication Data**
US 2016/0075131 A1 Mar. 17, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/529,927, filed on
Oct. 31, 2014, now Pat. No. 9,227,397, which is a
(Continued)

(30) Foreign Application Priority Data

Mar. 12, 2013 (JP) 2013-048836

(51) **Int. Cl.**
B41J 2/045 (2006.01)

(52) **U.S. Cl.**
CPC **B41J 2/04541** (2013.01); **B41J 2/04536**
(2013.01); **B41J 2/04581** (2013.01); **B41J**
2/04586 (2013.01); **B41J 2/04588** (2013.01)

(58) Field of Classification Search

CPC B41J 2/04536; B41J 2/04541; B41J 2/04581;
B41J 2/04586; B41J 2/04588
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

9,010,894 B2 * 4/2015 Yamamoto B41J 2/04541
347/10
9,227,397 B2 * 1/2016 Yamamoto B41J 2/04541
(Continued)

FOREIGN PATENT DOCUMENTS

JP 10-138473 A 5/1998
JP 2010-120328 A 6/2010
(Continued)

Primary Examiner — Alessandro Amari

Assistant Examiner — Roger W Pisha, II

(74) *Attorney, Agent, or Firm* — Global IP Counselors,
LLP

(57) ABSTRACT

A liquid ejection device includes a head unit and a control unit. A driving signal generating portion of the control unit is configured to create a driving signal having at least one wave portion for ejecting the liquid from the nozzles. A signal converting portion of the control unit is configured to convert plural types of original control signals including an original latching signal and an original printing data signal into a single serial control signal having a serial form. A signal restoring portion of the head unit is configured to create plural types of restored control signals from the serial control signal received, the restored control signals including a restored latching signal and a restored printing data signal. The nozzles are configured and arranged to eject the liquid based on the driving signal, the restored latching signal, and the restored printing data signal.

8 Claims, 3 Drawing Sheets

